



## Accrolube Multi-Vehicle with Moly

Accrolube Multi-Vehicle with Moly Grease is a high-performance lithium complex grease formulated for applications that require outstanding protection in extreme pressure, high load carrying applications. This unique formula is enhanced with molybdenum disulfide, a solid lubricant that will imbed in the metal surface and help reduce friction. The formula also contains polymer for improved adhesion properties at the interface.

Accrolube Multi-Vehicle with Moly Lubricant is a premium lubricant to meet the demands of today's heavy duty automotive and industrial applications.

Applications- Automotive disk-brakes, Wheel bearings, Chassis, Suspension, Universal joints.

BASE OIL CHARACTERISTICS			TYPICAL VALUE *
<b>Type</b>			<b>Mineral</b>
<b>Viscosity (ASTM D445 / DIN 51562-1)</b>	<b>at 100°C</b>		<b>16 cst</b>
	<b>at 40°C</b>		<b>170 cSt</b>
<b>Flash Point, °C, (ASTM D92)</b>			<b>221</b>
<b>Fire Point, °C (ASTM D92)</b>			<b>243</b>
<b>Pour Point, °C (ASTM D92)</b>			<b>-10</b>
<b>Viscosity Index (ASTM D2270)</b>			<b>99</b>
GREASE CHARACTERISTICS			TYPICAL VALUE *
<b>Thickener</b>			<b>Lithium Complex</b>
<b>Color</b>			<b>Gray/Black</b>
<b>Appearance</b>			<b>Smooth</b>
<b>NLGI Grade</b>			<b>2</b>
<b>Penetration (ASTM D217 / DIN 51804-T1)</b>	<b>Worked</b>	<b>60X</b>	<b>265-295</b>
<b>Dropping Point (°C) (ASTM D2265 / DIN ISO 2176)</b>			<b>260°C</b>
<b>Water Spray Off, % (ASTM D4049)</b>			<b>20</b>
<b>Copper Corrosion (ASTM D130 / DIN 51811)</b>			<b>24h at 100°C</b>
<b>Rust Test (ASTM D1743)</b>			<b>Pass</b>
<b>Four Ball Wear, mm (ASTM D2266)</b>			<b>0.50</b>
<b>Four Ball Weld, kg (ASTM D2596)</b>			<b>500</b>
<b>Oil Separation (ASTM D1742)</b>			<b>0.7</b>